

CBI Listing



CL 2302-04

Issue Date: March 2, 2023

Revision Date: March 2, 2023

Subject to Renewal: July 1, 2024

Trade Secret Owner

No-Burn®, Inc.

Website: www.noburn.com

Telephone: 800-989-8577

Email: info@noburn.com

DIVISION: 06 00 00 - WOOD, PLASTICS AND COMPOSITES

SECTION: 06 05 73 Fire Retardant Wood Treatment of Wood Products

DIVISION: 07 00 00 - THERMAL AND MOISTURE PROTECTION

SECTION: 07 80 00 - Fire and Smoke Protection

SECTION: 07 82 00 Board Fire Protection

DIVISION: 09 00 00 - FINISHES

SECTION: 09 23 82 Fire Protected Gypsum Plastering

SECTION: 09 96 43 - Fire-Retardant Coatings

SECTION: 09 96 46 - Intumescent Painting

1 Listed Innovative Product^{1,2}

1.1 No-Burn® Plus

¹ For more information, visit cbitest.com or call us at 608-310-6739.

² 24 CFR 3280.2 "Listed or certified" means included in a list published by a nationally recognized testing laboratory, inspection agency, or other organization concerned with product evaluation that maintains periodic inspection of production of listed equipment or materials, and whose listing states either that the equipment or material meets nationally recognized standards or has been tested and found suitable for use in a specified manner. **Listed.** Equipment, materials, products or services included in a list published by an organization acceptable to the building official and concerned with evaluation of products or services that maintains periodic inspection of production of listed equipment or materials or periodic evaluation of services and whose Listing states either that the equipment, material, product or service meets identified standards or has been tested and found suitable for a specified purpose. **Labeled.** Equipment, materials or products to which has been affixed a label, seal, symbol or other identifying mark of a nationally recognized testing laboratory, approved agency or other organization concerned with product evaluation that maintains periodic inspection of the production of the above-labeled items and whose labeling indicates either that the equipment, material or product meets identified standards or has been tested and found suitable for a specified purpose.

1.1.1 The Innovative Product evaluated in this Listing is shown in Figure 1.




Figure 1. No-Burn® Plus

- 1.2 No-Burn® Plus is a water-based, liquid applied, intumescent coating. When exposed to elevated temperatures and flame, it expands and forms a protective char layer.
- 1.3 No-Burn® Plus is packaged in either 5-gallon (18.9 liter) pails or 55-gallon (208 liter) drums.
- 1.4 No-Burn® Plus has a shelf life of two years when stored in unopened containers between 40°F (4.4°C) and 90°F (32.2°C) and kept out of direct sunlight.
- 1.5 No-Burn® Plus must be prepared with a power mixer (500-1500 RPM) or equivalent for a minimum of 5 minutes per container prior to application.
- 1.6 The substrates covered in this TER include the following:
 - 1.6.1 Douglas Fir (DF)
 - 1.6.2 Laminated Strand Lumber (LSL)
 - 1.6.3 Laminated Veneer Lumber (LVL)
 - 1.6.4 Oriented Strand Board (OSB)
 - 1.6.5 Southern Yellow Pine (SYP)
- 1.7 No-Burn® Plus protected OSB and lumber is acceptable for use in the following AWPAs³ Use Categories:
 - 1.7.1 UC1 – Interior construction – millwork and finishing
 - 1.7.2 UC2 – Interior construction – interior beams, timbers, flooring, framing, millwork, and sill plates

³ These are AWPAs designated wood preservation systems and retentions (pressure impregnation processes only) which have been determined to be effective in protecting wood products under specified exposure conditions. The use of No-Burn® Plus fire protective coating, while purposely not included in the AWPAs specification, satisfies and complies with the intent of the building code and is an equivalent treated material in quality, strength, effectiveness, durability, and safety. Therefore, No-Burn®, Inc. fire protective coating treated wood articles are deemed to be Non-AWPA Standardized; however, the intent of the building code has been satisfied and is adequately supported by third-party verified data and accredited testing protocols. See [IBC Section 104.11](#) for methods of obtaining "Alternative Materials Approval" via Building Official Authority.



1.8 Minimum coverage rates are specified in Table 1.

Table 1. Surface Burn Characteristics Minimum Coverage Rates

Product	Substrate	Application Rate	Maximum Moisture Content (%)
No-Burn® Plus	DF	6 mils wet (4 mils dry) 275 sq. ft. per gallon	19
	LSL	10 mils wet (6 mils dry) 160 sq. ft. per gallon	16
	LVL	10 mils wet (6 mils dry) 160 sq. ft. per gallon	16
	OSB	8 mils wet (5 mils dry) 200 sq. ft. per gallon	16
	SYP	10 mils wet (6 mils dry) 160 sq. ft. per gallon	19
Sl: 1 in = 25.4 mm			

2 Scope of Listing^{4,5}

2.1 No-Burn® Plus has been tested and/or evaluated in accordance with the following Standards and Referenced Documents for use as specified herein:

- 2.1.1 *ANSI/AWC NDS: National Design Specification (NDS) for Wood Construction*
- 2.1.2 *ASTM D3359: Standard Test Methods for Rating Adhesion by Tape Test*
- 2.1.3 *ASTM D4541: Standard Test Method for Pull-Off Strength of Coatings Using Portable Adhesion Testers*
- 2.1.4 *ASTM D4585: Standard Practice for Testing Water Resistance of Coatings Using Controlled Condensation*
- 2.1.5 *ASTM D610: Standard Practice for Evaluating Degree of Rusting on Painted Steel Surfaces*
- 2.1.6 *ASTM E84: Standard Test Method for Surface Burning Characteristics of Building Materials*
- 2.1.7 *ASTM E96: Standard Test Methods for Water Vapor Transmission of Materials*
- 2.1.8 *ASTM E119: Standard Test Methods for Fire Tests of Building Construction and Materials*
- 2.1.9 *ASTM E2768: Standard Test Method for Extended Duration Surface Burning Characteristics of Building Materials (30 min Tunnel Test)*
- 2.1.10 *ASTM G1: Standard Practice for Preparing, Cleaning, and Evaluating Corrosion Test Specimens*
- 2.1.11 *ASTM G85: Standard Practice for Modified Salt Spray (Fog) Testing*
- 2.1.12 *AWPA E12: Standard Method of Determining Corrosion of Metal in Contact with Treated Wood*
- 2.1.13 *NFPA 255: Standard Method of Test of Surface Burning Characteristics of Building Materials*

⁴ This Listing is a code defined research report, which is also known as a duly authenticated report, provided by an approved agency (see IBC Section 1703.1) and/or an approved source (see IBC Section 1703.4.2). An approved agency is “approved” as an approved agency when it is ANAB accredited (CBI and DrJ Engineering, LLC [DrJ] are listed in the ANAB directory). A professional engineer is “approved” as an approved source when that professional engineer is properly licensed to transact engineering commerce. Where sealed by a professional engineer, it is also a duly authenticated report certified by an approved source. (i.e., Registered Design Professional). CBI is an ANAB accredited laboratory and inspection body. DrJ is an ANAB accredited product certification body.

⁵ Unless otherwise noted, all references in this Listing are from the 2021 version of the codes and the standards referenced therein. This material, product, design, service and/or method of construction also complies with the 2000-2021 versions of the referenced codes and the standards referenced therein.



3 Performance Evaluation

- 3.1 Tests, testing, test reports, research reports, duly authenticated reports and related engineering evaluations are defined as intellectual property and/or trade secrets and protected by Defend Trade Secrets Act 2016 (DTSA).⁶
- 3.2 Testing and/or inspections conducted for this Listing were performed by CBI, an ISO/IEC 17025 accredited testing laboratory⁷ and ISO/IEC 17020 accredited inspection body,⁸ which are internationally recognized accreditations through International Accreditation Forum (IAF).
- 3.3 Independent testing and/or inspections conducted for this Listing were performed by an ISO/IEC 17025 accredited testing laboratory, ISO/IEC 17020 accredited inspection body, and/or a licensed Registered Design Professional (RDP).
- 3.4 *Fire Performance:*
 - 3.4.1 *Flame Spread and Smoke Developed Indexes*
 - 3.4.1.1 OSB or lumber protected by No-Burn® Plus meet the requirements where surface burning and smoke developed index values are required to be tested in accordance with ASTM E84 extended 20 minutes and ASTM E2768 (Table 2).

Table 2. Surface Burn Characteristics^{1,2,3}

Product	Substrate	Flame Spread	Smoke Developed
No-Burn® Plus	DF	≤ 25	≤ 450
	LSL		
	LVL		
	OSB		
	SYP		
1. Tested in accordance with ASTM E84, extended 20 minutes and ASTM E2768. 2. The flame front did not progress more than 10.5 feet beyond the centerline of the burners at any time during the test. 3. No-Burn® Plus may be over coated with paint.			

⁶ <https://www.law.cornell.edu/uscode/text/18/part-I/chapter-90>. As our professional duty to inform, please be aware that whoever, with intent to convert a trade secret (TS), that is related to a product or service used in or intended for use in interstate or foreign commerce, to the economic benefit of anyone other than the owner thereof, and intending or knowing that the offense will, injure any owner of that trade secret, knowingly without authorization copies, duplicates, sketches, draws, photographs, downloads, uploads, alters, destroys, photocopies, replicates, transmits, delivers, sends, mails, communicates, or conveys such information; shall be fined under this title or imprisoned not more than 10 years, or both. Any organization that commits any offense described in subsection (a) shall be fined not more than the greater of \$5,000,000 or 3 times the value of the stolen trade secret to the organization, including expenses for research and design and other costs of reproducing the trade secret that the organization has thereby avoided. The federal government and each state have a public records act. As the National Society of Professional Engineers states, "Engineers shall not disclose, without consent, confidential information concerning the business affairs or technical processes of any present or former client or employer, or public body on which they serve." Therefore, to protect intellectual property (IP) and TS, and to achieve compliance with public records and trade secret legislation, requires approval through the use of Listings, certified reports, technical evaluation reports, duly authenticated reports and/or research reports prepared by approved agencies and/or approved sources.

⁷ Internationally recognized accreditations are performed by members of the International Accreditation Forum (IAF). Accreditation Body and Regional Accreditation Group Members of IAF are admitted to the IAF MLA only after a stringent evaluation of their operations by a peer evaluation team, which is charged to ensure that the applicant complies fully with both international standards and IAF requirements. Once an accreditation body is a signatory of the IAF MLA, it is required to recognize certificates and validation and verification statements issued by conformity assessment bodies accredited by all other signatories of the IAF MLA, with the appropriate scope.

⁸ Ibid.

3.5 Fire Resistance

3.5.1 The No-Burn® Plus coated load bearing wall assembly described in Figure 2 and Table 2 met the requirements for a 120 minute fire resistance rating when tested in accordance with ASTM E119.




Figure 2. No-Burn® Plus 120 Minute Fire Resistance Rated Wall Assembly

3.5.2 Prior to installation of the insulation, No-Burn® Plus was applied at a wet film thickness of 12 – 14 mils to the three exposed sides of the studs and blocking and to the sheathing.

Table 3. No-Burn® Plus 120 Minute Fire Resistance Rated Wall Assembly Detail¹

Wall Component		Fastening Schedule
Interior Sheathing	5/8-inch thick Type X gypsum Wallboard, two layers	#6 x 1-5/8 in, coarse thread, bugle head drywall screw, 8:12 spacing
Insulation	R19 Kraft faced fiberglass batt	T50 x 1/2 in crown staples, 8 in o.c. spacing
No-Burn® Plus	12 – 14 mil wet film thickness	N/A
Framing	2x6 HF/DF/SYP 16 in o.c., double top plate, single bottom plate, blocking installed 24 in edge-to-center from the bottom plate and double top plate	3in x 0.131in smooth shank framing nails
Exterior Sheathing	7/16 in OSB	2-3/8 in x 0.113 in ring shank exterior nail, 6:12 spacing
Exterior Cladding	5/16 in thick fiber cement siding panels	2-3/8 in x 0.113 in ring shank exterior nail, 8:12 spacing

SI: 1 lb = 4.45 N
 1. Wall assembly tested in accordance with ASTM E119.

3.6 Water Vapor Transmission

3.6.1 No-Burn® Plus is vapor permeable and has the vapor permeance shown in Table 4.

Table 4. Vapor Permeance¹

Product	Permeance (perm)
No-Burn® Plus	5.06

1. Tested in accordance with ASTM E96.



3.7 *Water Resistance and Durability*

3.7.1 No-Burn® Plus does not chip, peel, crack, blister, or delaminate when exposed to high temperature and humidity conditions in accordance with ASTM D4585.

3.8 *Fastener Corrosion*

3.8.1 Common steel, red brass and aluminum fasteners are approved for use in substrates protected by No-Burn® Plus in accordance with ASTM D610, ASTM G1, ASTM G85, and AWWA E12.

3.9 *Chlorinated Polyvinyl Chloride (CPVC) Compatibility*

3.9.1 No-Burn® Plus has been tested and found to be compatible with CPVC, causing no detrimental effects. Therefore, No-Burn® Plus is approved for use in long-term contact with CPVC.

3.10 Any building code and/or accepted engineering evaluations (i.e., research reports, duly authenticated reports, etc.) that are conducted for this Listing were performed by DrJ Engineering, LLC (DrJ), an ISO/IEC 17065 accredited certification body and a professional engineering company operated by RDPs / approved sources. DrJ is qualified⁹ to practice product and code compliance services within its scope of accreditation and engineering expertise, respectively.

4 **Installation**

4.1 Installation shall comply with the manufacturer installation instructions, this Listing, the approved construction documents, and the applicable building code.

4.2 In the event of a conflict between the manufacturer installation instructions, this Listing, the approved construction documents and the applicable building code, the most restrictive shall govern.

4.3 *Installation Procedure*

4.3.1 The substrates that the No-Burn® Plus is applied to shall be clean, dry, and free from loose dirt, debris, grease, oil, or any other materials that would inhibit proper adhesion of No-Burn® Plus, including, but not limited to, any paints, stains, or sealants.

4.3.2 No-Burn® Plus is white in color.

4.3.3 Thickness measurements using a wet film thickness gauge shall be taken, at a minimum, once every 100 ft² (9.29 m²) of surface area during the application of each coat.

4.3.4 The dry mil thickness will be 0.6 to 0.7 times the wet mil thickness.

4.3.5 Apply No-Burn® Plus only to the substrates listed in Section 1.6 and Table 3 in accordance with the assembly selected.

4.3.6 Substrates shall be fully installed prior to application. No significant lag shall exist between application of No Burn® Plus and installation of weather protection.

4.3.7 Both the substrate surface and the ambient temperature shall be maintained between 40°F (4.4°C) and 100°F (37.7°C) immediately before and during application. Minimum cure time is 24 hours.

4.3.8 Apply the coating at the rate specified in Table 1 and Table 3.

4.3.9 Coating may be applied via roller, brush, or spraying equipment.

4.3.10 After curing, the coating may be over-coated with latex paint per the paint manufacturer instructions.

4.3.11 The installation certificate provided in Appendix B shall be completed by the certified applicator and submitted to No-Burn®, Inc. and other interested parties.

⁹ Qualification is performed by a legislatively defined Accreditation Body. ANSI National Accreditation Board (ANAB) is the largest independent accreditation body in North America and provides services in more than 75 countries. CBI is an ANAB accredited laboratory and inspection body. DrJ is an ANAB accredited product certification body.



5 Findings

- 5.1 As described in Section 3, No-Burn® Plus has performance characteristics that were tested and/or meet pertinent standards and is suitable for use pursuant to its specified purpose.
- 5.2 When used and installed in accordance with this Listing and the manufacturer installation instructions, No-Burn® Plus shall be approved for:
 - 5.2.1 No-Burn® Plus protection does not affect the allowable design stresses allowed for untreated OSB and lumber.
 - 5.2.2 The No-Burn® Plus coated load bearing wall assembly described in Figure 2 and Table 3 met the requirements for a 120 minute fire resistance rating when tested in accordance with ASTM E119.
 - 5.2.3 OSB and lumber protected with No-Burn® Plus meet the requirements where surface burning characteristics are required to be in accordance with ASTM E84 extended 20 minutes, ASTM E2768, and NFPA 255.
 - 5.2.4 No-Burn® Plus meets the required water vapor transmission properties for a Class III vapor retarder.
 - 5.2.5 No-Burn® Plus protected OSB and lumber meet the water resistance requirements of ASTM D4585.
 - 5.2.6 The degradation rate of CPVC is not increased by long-term contact with No-Burn® Plus protected OSB and lumber.
- 5.3 Unless exempt by state statute, when No-Burn® Plus is to be used as a structural and/or building envelope component in the design of a specific building, the design shall be performed by an RDP.
- 5.4 Any application specific issues not addressed herein can be engineered by an RDP. Assistance with engineering is available from No-Burn®, Inc.
- 5.5 IBC Section 104.11 (IRC Section R104.11 and IFC Section 104.10¹⁰ are similar) in pertinent part states:

104.11 Alternative materials, design and methods of construction and equipment. The provisions of this code are not intended to prevent the installation of any material or to prohibit any design or method of construction not specifically prescribed by this code. Where the alternative material, design or method of construction is not approved, the building official shall respond in writing, stating the reasons the alternative was not approved.
- 5.6 Approved:¹¹ Building codes require that the building official shall accept duly authenticated reports¹² or research reports¹³ from approved agencies and/or approved sources (i.e., licensed RDP) with respect to the quality and manner of use of new products, materials, designs, services, assemblies, or methods of construction.
- 5.6.1 Acceptability of an approved agency, by a building official, is performed by verifying that the agency is accredited by a recognized accreditation body of the International Accreditation Forum (IAF).
- 5.6.2 Acceptability of a licensed RDP by a building official is performed by verifying that the RDP and/or their business entity is listed by the licensing board of the relevant jurisdiction.
- 5.7 CBI is an ISO/IEC 17025 testing and an ISO/IEC 17020 inspection approved agency. CBI employs RDPs and is ANAB-Accredited.

¹⁰ 2018 IFC Section 104.9

¹¹ Approved is an adjective that modifies the noun after it. For example, Approved Agency means that the Agency is accepted officially as being suitable in a particular situation. This example conforms to IBC/IRC/IFC Section 201.4 where the building code authorizes sentences to have an ordinarily accepted meaning such as the context implies.

¹² <https://up.codes/viewer/wyoming/ibc-2021/chapter/17/special-inspections-and-tests#1707.1>

¹³ <https://up.codes/viewer/wyoming/ibc-2021/chapter/17/special-inspections-and-tests#1703.4.2>



- 5.8 Through ANAB accreditation and the IAF Multilateral Agreements, this Listing can be used to obtain innovative product approval in any jurisdiction or country that has IAF MLA Members and Signatories to meet the Purpose of the MLA – “certified once, accepted everywhere.” IAF specifically says, “Once an accreditation body is a signatory of the IAF MLA, it is required to recognise certificates and validation and verification statements issued by conformity assessment bodies accredited by all other signatories of the IAF MLA, with the appropriate scope.”¹⁴

6 Conditions of Use

- 6.1 Performance characteristics are specified in Section 3.
- 6.2 As defined in Section 3, where material or engineering mechanics properties are created for load resisting design purposes, the resistance to the applied load shall not exceed the ability of the defined properties to resist those loads using the principles of accepted engineering practice.
- 6.3 For field-applied applications, the certified applicator shall provide documentation that the application rate meets the requirements listed in Table 1 and Table 3.
- 6.4 An installation certificate provided in Appendix B shall be completed by the certified applicator and submitted to No-Burn®, Inc. and other interested parties. As listed herein, No-Burn® Plus shall be used:
- 6.4.1 In applications limited to DF, LSL, LVL, OSB, and SYP.
 - 6.4.2 For above ground applications not subject to continuous contact with liquid water.
 - 6.4.3 Only with fastener design values that were determined using the specific gravity of the OSB or lumber species used in the coated product.
 - 6.4.4 In accordance with the limitations of the applicable building code for sawn lumber when determining duration of load increases. However, this may never be greater than 1.6.
- 6.5 Cutting and notching of No-Burn® Plus coated OSB or lumber is permitted where allowed by the applicable building code, the manufacturer recommendations, this TER, or where the effects of such alterations are specifically considered in the design of the member by a registered design professional.
- 6.6 When required by adopted legislation and enforced by the building official (AHJ)¹⁵ in which the project is to be constructed:
- 6.6.1 This Listing and the installation instructions shall be submitted at the time of permit application.
 - 6.6.2 Any calculations incorporated into the construction documents shall conform to accepted engineering practice and, when prepared by an approved source, shall be approved when requirements of adopted legislation are met.
 - 6.6.3 This Innovative Product has an internal quality control program and a third-party quality assurance program.
 - 6.6.4 At a minimum, this innovative product shall be installed per Section 4 of this Listing.
- 6.7 The approval of this Listing by the AHJ shall comply with IBC Section 1707.1, where legislation states in pertinent part, “the building official shall accept duly authenticated reports from approved agencies in respect to the quality and manner of use of new materials or assemblies as provided for in IBC Section 104.11”, all of IBC Section 104, and IBC Section 105.4.
- 6.8 This Innovative Product has an internal quality control program and a third party quality assurance program in accordance with IBC Section 104.4, IBC Section 110.4, IBC Section 1703, IRC Section R104.4, and IRC Section R109.2.

¹⁴ <https://iaf.nu/en/about-iaf-mla/#:~:text=required%20to%20recognise>

¹⁵ Also known as the Authority Having Jurisdiction (AHJ)



- 6.9 The application of this Innovative Product, in the context of this Listing, is dependent upon the accuracy of the construction documents, implementation of installation instructions, inspection as required by [IBC Section 110.3](#), [IRC Section R109.2](#), and any other regulatory requirements that may apply.
- 6.10 The actual design, suitability, and use of this Listing for any particular building is the responsibility of the owner or the owner's authorized agent.
- 6.11 Any required design loads shall be provided by the building designer (i.e., owner or RDP) and/or determined in accordance with the building code adopted by the jurisdiction in which the project is to be constructed.
- 6.12 Information contained herein may include the result of testing and/or data analysis by sources that are [approved agencies](#) (i.e., ANAB accredited agencies), [approved sources](#) (i.e., RDPs), and/or [professional engineering regulations](#). Accuracy of external test data and resulting analysis is relied upon.
- 6.13 Where pertinent, testing and/or engineering analysis is based upon state or local code and/or standard provisions that have been codified into law through legislation. The developers of the codes and standards are legally responsible for the accuracy of any legislatively adopted material properties and/or analytical methods. Any testing and/or engineering mechanics-based analysis may use legislatively and/or code adopted provisions as the control condition. The use of a control condition to compare to a test condition establishes [equivalency](#) to that prescribed in the adopted legislation with respect to quality, [strength](#), effectiveness, [fire resistance](#), durability, and safety.
- 6.14 The reliability of the attributes provided herein may be dependent upon published design properties by others. These properties are defined by the grade mark, grade stamp, mill certificate, [Listings](#), [certified reports](#), [duly authenticated reports](#), and/or [research reports](#) prepared by [approved agencies](#) and/or [approved sources](#) furnished by suppliers of products, materials, designs, assemblies, and/or methods of construction. These are presumed to be minimum properties and relied upon to be accurate.
- 6.15 Testing and engineering analysis: The strength, rigidity and/or general performance of component parts and/or the integrated structure are determined by suitable tests that simulate the actual conditions of application that occur and/or by accepted engineering practice and experience.¹⁶
- 6.16 Where additional condition of use and/or code compliance information is required, please search for No-Burn® Plus on the [DrJ Engineering](#) website.

7 Identification

- 7.1 Labeling^{17,18} shall include, but not be limited to, the manufacturer name, manufacturing location/identifier, and the CBI Listing number.
- 7.2 Labeling may include, but not be limited to, the CBI mark and any other numerical designations related to layout locations for a given project.

8 Review Schedule

- 8.1 This Listing is subject to periodic review and revision. For the most recent version, visit [cbitest.com](#).
- 8.2 For information on the status of this Listing, contact [CBI](#).

¹⁶ See Code of Federal Regulations (CFR) [Title 24 Subtitle B Chapter XX Part 3280](#) for definition.

¹⁷ [LABEL](#): An identification applied on a product by the manufacturer that contains the name of the manufacturer, the function and performance characteristics of the product or material and the name and identification of an [approved agency](#), and that indicates that the representative sample of the product or material has been tested and evaluated by an [approved agency](#) (see [IBC Section 1703.5](#), "[Manufacturer designation](#)" and "Mark").

¹⁸ [LABELED](#): Equipment, materials or products to which has been affixed a [label](#), seal, symbol or other identifying mark of a nationally recognized testing laboratory, [approved agency](#) or other organization concerned with product evaluation that maintains periodic inspection of the production of the above-[labeled](#) items and whose labeling indicates either that the equipment, material or product meets identified standards or has been tested and found suitable for a specified purpose.



9 Approved for Use Pursuant to US and International Legislation Defined in Appendix A

- 9.1 No-Burn® Plus is included in this [list](#) published by an [approved agency](#) concerned with evaluation of products or services that maintains periodic inspection of production of listed materials or periodic evaluation of services and whose Listing states either that the material, product, or service meets identified standards or has been tested and found suitable for a specified purpose. This Listing meets the legislative intent and definition of being acceptable to the AHJ.



1 Appendix A: Innovation Legislation that Mandates Approval by any AHJ

- 1.1 **Fair Competition:** Many state legislatures have adopted regulations for the examination and approval of both building codes referenced and alternative materials, products, designs, services, and/or methods of construction that:
 - 1.1.1 Advance innovation,
 - 1.1.2 Promote competition so all businesses have the opportunity to compete on price and quality in an open market on a level playing field unhampered by anticompetitive constraints, and
 - 1.1.3 Benefit consumers through lower prices, better quality, and greater choice.
- 1.2 **Adopted Legislation:** The following local, state, and federal regulations affirmatively authorize No-Burn® Plus to be found acceptable to AHJs, delegates of building departments, and/or delegates of an agency of the federal government:
 - 1.2.1 Interstate commerce is governed by the Federal Department of Justice to encourage the use of innovative materials, products, designs, services, and/or methods of construction. The goal is to “protect economic freedom and opportunity by promoting free and fair competition in the marketplace.”
 - 1.2.2 Title 18 US Code Section 242 affirms and regulates the right of individuals and businesses to freely and fairly have alternative to code-referenced materials, products, services, designs, and/or methods of construction approved for use in commerce. Disapproval of alternative to code applications shall be based upon specific provisions of adopted legislation and shall be provided in writing stating the reasons why the alternative was not approved with reference to legislation violated.
 - 1.2.3 The federal government and each state have a public records act. In addition, each state also has legislation that mimics the federal Defend Trade Secrets Act 2016 (DTSA).
 - 1.2.3.1 Compliance with public records and trade secret legislation requires approval through the use of Listings, certified reports, duly authenticated reports from approved agencies, valid research reports prepared by approved agencies and/or approved sources, and/or Technical Evaluation Reports.
 - 1.2.4 For new materials that are not specifically provided for in any building code, the design strengths and permissible stresses shall be established by tests, where suitable load tests simulate the actual loads and conditions of application that occur.
 - 1.2.5 The design strengths and permissible stresses of any structural material....shall conform to the specifications and methods of design using accepted engineering practice....¹⁹
 - 1.2.6 The commerce of approved sources (i.e., registered PEs) is regulated by professional engineering legislation. Professional engineering commerce shall always be approved by AHJs, except where there is evidence, provided in writing, that specific legislation has been violated by an individual registered PE.
 - 1.2.7 The AHJ shall accept duly authenticated reports from approved agencies in respect to the quality and manner of use of new materials or assemblies as provided for in IBC Section 104.11.²⁰

¹⁹ IBC 2021, Section 1706.1 Conformance to Standards

²⁰ IBC 2021, Section 1707 Alternative Test Procedure, 1707.1 General



- 1.3 **Approval by Los Angeles:** The Los Angeles Municipal Code (LAMC) states in pertinent part that the provisions of LAMC are not intended to prevent the use of any material, device, or method of construction not specifically prescribed by LAMC. The Department shall use Part III, Recognized Standards in addition to Part II, Uniform Building Code Standards of Division 35, Article 1, Chapter IX of the LAMC in evaluation of products for approval where such standard exists for the product or the material and may use other approved standards which apply. Whenever tests or certificates of any material or fabricated assembly are required by Chapter IX of the LAMC, such tests or certification shall be made by a testing agency approved by the Superintendent of Building to conduct such tests or provide such certifications. The Superintendent of Building shall accept duly authenticated reports from approved agencies in respect to the quality and manner of use of new materials or assemblies as provided for in the California Building Code (CBC) Section 104.11. The testing agency shall publish the scope and limitation(s) of listed material or fabricated assembly.²¹ The Superintendent of Building roster of approved testing agencies is provided by the Los Angeles Department of Building and Safety (LADBS).
- 1.4 **Approval by Chicago:** The Municipal Code of Chicago (MCC) states in pertinent part that an Approved Agency is a Nationally Recognized Testing Laboratory (NRTL) acting within its recognized scope and/or a certification body accredited by the American National Standards Institute (ANSI) acting within its accredited scope. Construction materials and test procedures shall conform to the applicable standards listed in the MCC. Sufficient technical data shall be submitted to the building official to substantiate the proposed use of any product, material, or assembly. Supporting technical data to assist in the approval of products, materials, or assemblies not specifically provided for in MCC, shall consist of valid research reports from approved sources (i.e., MCC defined Approved Agencies).
- 1.5 **Approval by New York City:** The NYC Building Code 2022 (NYCBC) states in pertinent part that an approved agency shall be deemed²² an approved testing agency via ISO/IEC 17025 accreditation, an approved inspection agency via ISO/IEC 17020 accreditation, and an approved product evaluation agency via ISO/IEC 17065 accreditation. Accrediting agencies, other than federal agencies, must be members of an internationally recognized cooperation of laboratory and inspection accreditation bodies subject to a mutual recognition agreement²³ (i.e., ANAB, International Accreditation Forum (IAF), etc.).
- 1.6 **Approval by Florida:** Statewide approval of products, methods, or systems of construction shall be approved, without further evaluation, by 1) A certification mark or listing of an approved certification agency, 2) A test report from an approved testing laboratory, 3) A product evaluation report based upon testing or comparative or rational analysis, or a combination thereof, from an approved product evaluation entity; 4) A product evaluation report based upon testing or comparative or rational analysis, or a combination thereof, developed and signed and sealed by a professional engineer or architect, licensed in Florida. For local product approval, products or systems of construction shall demonstrate compliance with the structural wind load requirements of the Florida Building Code (FBC) through one of the following methods; 1) A certification mark, listing, or label from a commission-approved certification agency indicating that the product complies with the code; 2) A test report from a commission-approved testing laboratory indicating that the product tested complies with the code; 3) A product-evaluation report based upon testing, comparative or rational analysis, or a combination thereof, from a commission-approved product evaluation entity which indicates that the product evaluated complies with the code; 4) A product-evaluation report or certification based upon testing or comparative or rational analysis, or a combination thereof, developed and signed and sealed by a Florida professional engineer or Florida registered architect, which indicates that the product complies with the code; 5) A statewide product approval issued by the Florida Building Commission. The Florida Department of Business and Professional Regulation (DBPR) website provides a listing of companies certified as a Product Evaluation Agency (i.e., EVL13692), a Product Certification Agency (i.e., CER10642), and as a Florida Registered Engineer (i.e., ANE13741).

²¹ Los Angeles Municipal Code, SEC. 98.0503. TESTING AGENCIES

²² New York City, The Rules of the City of New York, § 101-07 Approved Agencies

²³ New York City, The Rules of the City of New York, § 101-07 Approved Agencies



- 1.7 **Approval by Miami Dade (i.e., Notice of Acceptance [NOA]):** A Florida statewide approval is an NOA. An NOA is a Florida local product approval. By Florida law, Miami Dade shall accept the statewide and local Florida Product Approval as provided for in Florida legislation [553.842](#) and [553.8425](#).
- 1.8 **Approval by New Jersey:** Pursuant to Building Code 2018 of New Jersey in [Section 1707.1 General](#)²⁴ says: “In the absence of approved rules or other approved standards,...the building official shall accept duly authenticated reports from [approved agencies](#) in respect to the quality and manner of use of new materials or assemblies as provided for in the administrative provisions of the [Uniform Construction Code \(N.J.A.C. 5:23\)](#)”²⁵. § 5:23-3.7 Municipal approvals of alternative materials, equipment, or methods of construction. (a) Approvals: Alternative materials, equipment, or methods of construction **shall be approved** by the appropriate subcode official provided the proposed design is satisfactory and that the materials, equipment, or methods of construction are suitable for the intended use and are at least the equivalent in quality, strength, effectiveness, fire resistance, durability and safety of those conforming with the requirements of the regulations. 1. A field evaluation label and report or letter issued by a nationally recognized testing laboratory verifying that the specific material, equipment, or method of construction meets the identified standards or has been tested and found to be suitable for the intended use, **shall be accepted** by the appropriate subcode official as meeting the requirements of (a) above. 2. Reports of engineering findings issued by nationally recognized evaluation service programs, such as, **but not limited to**, the Building Officials and Code Administrators (BOCA), the International Conference of Building Officials (ICBO), the Southern Building Code Congress International (SBCCI), the International Code Council (ICC), and the National Evaluation Service, Inc., **shall be accepted** by the appropriate subcode official as meeting the requirements of (a) above. The [New Jersey Department of Community Affairs](#) has confirmed that reports of engineering findings from any accredited entity listed by [ANAB](#) meets the requirements of item 2 given the listed entities no longer exist.
- 1.9 **Code of Federal Regulations Manufactured Home Construction and Safety Standards Approval:** Pursuant to Title 24, Subtitle B, Chapter XX, [Part 3282](#)²⁶ and [Part 3280](#)²⁷, “*the Department encourages innovation and the use of new technology in manufactured homes*” and the design and construction of a manufactured home shall conform to the provisions of this standard where key approval provisions in mandatory language follow; “*All construction methods shall be in conformance with accepted engineering practices*”, “*the strength and rigidity of the component parts and/or the integrated structure shall be determined by engineering analysis or by suitable load tests to simulate the actual loads and conditions of application that occur*”, and “*the design stresses of all materials shall conform to accepted engineering practice*”.
- 1.10 **Other US Local and State Approval Processes:** In all other local and state jurisdictions, the adopted building code legislation states in pertinent part that:
 - 1.10.1 For [new materials](#) that are not specifically provided for in this code, the [design strengths and permissible stresses](#) shall be established by tests.²⁸
 - 1.10.2 For [innovative alternative products, materials, designs, services and/or methods of construction](#), in the absence of approved rules or other approved standards...the building official shall accept [duly authenticated reports](#) (i.e., listing and/or research report) from [approved agencies](#) with respect to the quality and manner of use of [new materials or assemblies](#).²⁹ A building official [approved agency](#) is deemed to be approved via certification from an [accreditation body](#) that is listed by the [International Accreditation Forum](#),³⁰ or the equivalent.

²⁴ https://up.codes/viewer/new_jersey/lbc-2018/chapter/17/special-inspections-and-tests#1707.1

²⁵ <https://www.nj.gov/dca/divisions/codes/codereg/ucc.html>

²⁶ <https://www.ecfr.gov/current/title-24/subtitle-B/chapter-XX/part-3282/subpart-A/section-3282.14>

²⁷ <https://www.ecfr.gov/current/title-24/subtitle-B/chapter-XX/part-3280>

²⁸ [IBC 2021, Section 1706 Design Strengths of Materials, 1706.2 New Materials](#). Adopted law pursuant to IBC model code language 1706.2.

²⁹ [IBC 2021, Section 1707 Alternative Test Procedure, 1707.1 General](#). Adopted law pursuant to IBC model code language 1707.1.

³⁰ Please see the [ANAB directory](#) for building official approved agencies.



- 1.10.3 The design strengths and permissible stresses of any structural material...shall conform to the specifications and methods of design of accepted engineering practice performed by an approved source.³¹ An approved source is defined as a PE subject to professional engineering laws, where a research and/or a technical evaluation report, certified by a PE, shall be approved.
- 1.11 **International Approval Process:** The USMCA and GATT agreements provide for approval of innovative materials, products, designs, services, and/or methods of construction through the Technical Barriers to Trade agreements and the International Accreditation Forum (IAF) Multilateral Recognition Arrangement (MLA), where these agreements state in pertinent part:
- 1.11.1 Permit participation of conformity assessment bodies located in the territories of other Members under conditions no less favourable than those accorded to bodies located within their territory or the territory of any other country.
- 1.11.2 Conformity assessment procedures (i.e., ISO/IEC 17020, 17025, 17065, etc.) are prepared, adopted, and applied so as to grant access for suppliers of like products originating in the territories of other Members under conditions no less favourable than those accorded to suppliers of like products of national origin or originating in any other country, in a comparable situation.
- 1.11.3 Conformity assessment procedures are not prepared, adopted, or applied with a view to or with the effect of creating unnecessary obstacles to international trade. This means that conformity assessment procedures shall not be more strict or be applied more strictly than is necessary to give the importing Member adequate confidence that products conform to the applicable technical regulations or standards.
- 1.11.4 **International Approval:** The purpose of the IAF MLA is to ensure mutual recognition of accredited certification and validation/verification statements between signatories to the MLA, and subsequently acceptance of accredited certification and validation/verification statements in many markets based on one accreditation for the timely approval of innovative materials, products, designs, services, and/or methods of construction. Accreditations granted by IAF MLA signatories are recognized worldwide based on their equivalent accreditation programs, therefore reducing costs and adding value to businesses and consumers.

³¹ IBC 2021, Section 1706 Design Strengths of Materials, 1706.1 Conformance to Standards Adopted law pursuant to IBC model code language 1706.1.



Appendix B
NO-BURN® PRODUCT APPLICATION CERTIFICATE

LOCATION OF BUILDING:

Address	Lot #	City	State	Zip
----------------	--------------	-------------	--------------	------------

DESCRIPTION AND USE OF BUILDING:

Certified Applicator Name	Company	Certified Applicator Number
----------------------------------	----------------	------------------------------------

Moisture Meter Reading (Max % Noted in Table 1 & Table 3)	Temp Reading (°F)	Describe Area Treated	Size of Area Treated (Surface Area, Sq. Ft.)	Product Applied	Substrate (Noted in Table 1 & Table 3)	Qty. (Wet film thickness)	Date Applied

Certified Applicator Signature	Date of Service
---------------------------------------	------------------------